



Product Name

LIGHTHOUSE LIGHTWEIGHT SPACKLING COMPOUND (L422-1)

Product Description

LIGHTHOUSE LIGHTWEIGHT SPACKLING COMPOUND is a smooth, water-based, remixed product for use in patching holes, dents, scratches, and other defects on interior or exterior substrates. It is easy to apply, tool and sand. Cleans up with soap and water.

Basic Uses

Uses: LIGHTHOUSE LIGHTWEIGHT SPACKLING COMPOUND may be used to patch non-structural defects in wood, plaster, sheetrock, stucco, and masonry.

Technical Data

| Property | Value | Test Method |
|-------------------------|--------------------|--------------------|
| % Solids by Weight | 39.5% ± 1% Minimum | Lab Value |
| % Solids by Volume | 69.0% ± 1% | Lab Value |
| Viscosity: Equilibrated | 75000 ± 5000 | |

Typical product data values should not be used as specifications.

Limitations

- Do not use for structural repairs.
- Interior/Exterior. For exterior use product must be painted with high quality paint for the best performance.
- Do not use below grade or under water.
- Application should be made when temperature of air and surface is 50°F. (10°C.) or above.
- Do not apply if relative humidity is above 90%.
- Do not freeze.

Surface Preparation

Surface must be firm and free of moisture, dirt, oil, grease, mildew, wax and loose material. Apply only when spackling compound and surface temperatures are above 50°F (10°C). New or unpainted porous surfaces should be primed and allowed to dry before patching.

Method of Application

Apply with putty knife or broad knife and press firmly into open space. For larger holes, stuff the hole with newspaper prior to patching to provide more even drying. Clean up with soap and water. Can be lightly sanded when completely dry to even out the surface profile.

Packaging: 1 gallon (4 per case), Quart (6 per case) and Half-pint (24 per case).

When using, do not keep in direct sunlight for prolonged periods. KEEP FROM FREEZING. KEEP OUT OF REACH OF CHILDREN.

Clean Up

Clean all equipment immediately after use with warm, soapy water.

Handling and Safety

Material Safety Data Sheets (MSDS) are available upon request from Momentive Performance Materials. Similar information for solvents and other chemicals used with Momentive Performance Materials products should be obtained from your suppliers. When solvents are used, proper safety precautions must be observed. Do not breathe mist. Use only in well ventilated area. Wear respiratory protection if exposure to vapor or mist from processing is possible. KEEP OUT OF REACH OF CHILDREN.

Warranty

Momentive Performance Materials warrants the performance of this product, provided it is properly stored and applied before the "use before" date shown. If not satisfied, return product and/or proof of purchase to address below and Momentive Performance Materials will, at its option, replace or refund the purchase price of this product. MOMENTIVE PERFORMANCE MATERIALS shall in no event be liable for any other damages in excess of the amount of the purchase price. THIS IS THE SOLE AND EXCLUSIVE REMEDY FOR DEFECTS IN, OR FAILURE OF, THIS PRODUCT, AND THE SOLE AND EXCLUSIVE LIABILITY OF MOMENTIVE PERFORMANCE MATERIALS COMPANY THEREFOR. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES WRITTEN OR ORAL, STATUTORY, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF THE MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright 2011 Momentive Performance Materials Inc., all rights reserved.